



"KIRAN " CEMENT PRIMER WHITE

Cement Primer is formulated with a special binder to withstand Residual alkali that is present in cement concrete walls. The Binder and pigments are resistance to mild alkali and have an excellent filling properties to prevent excessive absorption of Subsequent coats. It is an excellent primer suitable for both Water borne paints and flat oil and synthetic enamels etc.

TECHNICAL DETAILS

1) Consistency	Smooth and Uniform.
2) Specific Gravity	1.35 kg.
3) Color	White.
4) Drying Time	Touch dry 2 hrs, Hard dry 6 hrs.
5) Flexibility & Adhesion	Good.
6) Flash Point	30 C.
7) Viscosity	80 to 100 seconds.
8) Filling Properties	Excellent.
9) Covering Capacity	10 to 15 sq meters per litre.
10) Can stability	One year from date of manufacture.
11) Remarks	An ideal cement primer for cement concrete walls which are matured by atleast six months after the construction.

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE**

KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.
Office : 501, Madhav Apt., Jawahar Road, Ghatkopar (East), Mumbai-400077, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101
Office Tel.: 91-22-25132776 / 25123780 Fax: 91-22-25154958
Email : sales@kiranpaints.com / dvrkiran@bom3.vsnl.net.in
Website : www.kiranpaints.com