



CEMENT PRIMER WHITE

Cement Primer is formulated with a special binder to withstand Residual alkali that is present in cement concrete walls. The Binder and pigments are resistance to mild alkali and have an Excellent filling properties to prevent excessive absorption of Subsequent coats. It is an excellent primer suitable for both Water borne paints and flat oil and synthetic enamels etc.

TECHNICAL DETAILS

- | | |
|---------------------------|--|
| 1) Consistency | : Smooth and Uniform. |
| 2) Specific Gravity | : 1.35 kg. |
| 3) Color | : White. |
| 4) Drying Time | : Touch dry 2 hrs,
Hard dry 6 hrs. |
| 5) Flexibility & Adhesion | : Good. |
| 6) Flash Point | : 30 C. |
| 7) Viscosity | : 80 to 100 seconds. |
| 8) Filling Properties | : Excellent. |
| 9) Covering Capacity | : 10 to 15 sq meters per litre. |
| 10) Can stability | : One year from date of manufacture. |
| 11) Remarks | : An ideal cement primer for cement
Concrete walls which are matured
by at least six months after the
Construction. |

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE

KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330

Email : info@kiranpaints.com

Website : www.kiranpaints.com