



KIRAN HEAT RESISTING LUSTROL ALUMINIUM

A high luster two-pack Aluminum Paint with Remarkable protective properties and heat resistance up to 290 C. This is suitable as a heat resistant coating for chimneystacks, boiler fronts, ductwork, and piping and furnace structure. As general-purpose aluminum paint it shows excellent performance in both internal and external application in buildings, offices, factories, industrial plants, warehouses etc. It has special use in coating exterior of storage tanks in oil industry because of its higher reflectance value.

Colour	Aluminum
Finish	Bright metallic
Mixing	Aluminum Paste and Medium supplied in proportionate quantities. Mixed Paint to be used off within 48 hours
Volume Solid Fraction	0.23 Approximately
Recommended dry film thickness	15 microns
Corresponding wet film thickness	65 microns
Theoretical spreading rate	15.3 Sq. Metre per liter
Coverage with loss factor 20%	12.2 Sq. " " "
Coverage with loss factor 30%	10.7 Sq. " " "
Coverage with loss factor 40%	9.2 Sq. " " "
Drying Time	Touch dry in 4 hours Hard dry in 12 hours
Interval before Overcoating	24 hours minimum No Maximum
Method of application	Brush/ Roller/Spray
Thinner	Kiran HR. THINNER
Storage life	9 month keep in dry place
Surface preparation	Surface must be clean, dry free from dust & grease.
As heat resistant coating above 100 C paint to be applied Directly on cleaned metal surface.	
For other uses (below 100 C) the paint Should go on appropriate primer	
Notes on Airless Spray	Tip range- 13-16 thou. Total output fluid pressure 2500 pi (176-211 kg/sq.cm.)
Uses	Buildings Structures, Industrial Plants, Chimney Stacks Petrol-Chemical and Water Tanks, Pipes etc.

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE**



KIRAN PAINTS PVT. LTD.



KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.
Office : 501, Madhav Apt., Jawahar Road, Ghatkopar (East), Mumbai-400077, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101
Office Tel.: 91-22-25132776 / 25123780 Fax: 91-22-25154958
Email : sales@kiranpaints.com / dvrkiran@bom3.vsnl.net.in
Website : www.kiranpaints.com