



Q.D. ROAD MARKING PAINT (QRM)

1-UP QRM possesses the excellent color, gloss retention properties. The binder use in QRM is modified with resins to give quick dry and provide flexible and tough films. It can be use on both concrete as well as tar base road.

Type	: One pack.
Pot life	: 4 to 6 hours.
Drying Period	: Touch Dry: 5 minutes : Hard Dry: 3 hrs. Depending on climatic condition.
Viscosity	: 60 to 80 seconds in ford cup No.4.
Volume Solid	: 64% apex.
Application	: Brush or Rolling Wheel
Recommended DFT	: 30 to 45 microns.
Theoretical spreading rate	: 10 to 12 sq. mtr/ltr.
Color	: White, Yellow, Grey, Pink & Black.
Thinner	: Kiran QRM Thinner.
Packing	: 20/4/2/1 liters.
Finish	: Eggshell , Reflective, Glossy.
Storage	: Up to 6 months as long as sealed container : Kept in dry & cool place.

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE**

KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330

Email : info@kiranpaints.com

Website : www.kiranpaints.com