



## **HB THERMOPLASTIC ROAD MARKING PAINT (TRM)**

1-UP HB TRM possesses excellent Road Marking properties. The binders used in TRM are selected to provide hard and tough film, yet with sufficient plasticising characteristic to maintain flexibility and it also contains silica beads for utmost reflection. Thus it's life as road-marking paint is long lasting for any type of roads including Concrete and Bituminous based Roads.

|                             |   |
|-----------------------------|---|
| Type:                       | One pack  |
| Drying Period:              | Touch dry: 5-10 minutes<br>Hard dry: 1 to 2 hrs maximum                                 |
| Viscosity:                  | 60 +/- 10 Seconds. In ford cup # 4  |
| Solid Content:              | 63 +/- 10% app.   |
| Application:                | Brush, Roller or Rolling wheel  |
| Recommended DFT:            | 45 microns +/- 5  |
| Theoretical Spreading Rate: | 7 +/- 2 sq./Mt. P/lt.   |
| Color:                      | White, Yellow, and any standard shade   |
| Thinner:                    | 1-UP TRM Thinner  |
| Finish:                     | Reflective glossy   |
| Storage:                    | up to Nine months from date of mfg. As long as sealed container kept in dry cool place. |

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH  
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE**

KIRAN PAINTS PVT. LTD.  
Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.  
Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330  
Email : [info@kiranpaints.com](mailto:info@kiranpaints.com)  
Website : [www.kiranpaints.com](http://www.kiranpaints.com)