



Super Synthetic Enamel for Exterior use generally

Conforming to IS 2932.

These Synthetic Enamels are processed in our equipments like Sand Mills and Bead Mills at a controlled temperature with modern wetting And dispersing agents to give maximum opacity obliteration These enamels have an excellent durability and gloss. They have proven life for exterior performance.

TECHNICAL DETAILS

Consistency : Smooth and uniform.
Specific gravity : 0.90 - 1.05 kg.
Color : As required by customers or
: as per our standard shade cards.
Drying Time : Touch dry 4 hrs, Hard dry 10 hrs.
Flexibility & Adhesion : Good.
Flash Point : 30 degree cent.
Viscosity : 90 to 120 seconds.
Gloss : Excellent.
Alkali resistance : Passes when tested as per IS 101.
Acid resistance : Passes when tested as per Is 101.
Resistance to water : Excellent.
Durability : Passes 21 days weatherometer.
Covering Capacity : 15 to 20 sp meter per liter depending
: Upon the colors.
Can Stability : One year from date of manufacture.
Remarks : These are excellent exterior synthetic
: Enamels for protecting railways
: Coaches bus bodies etc. on a system
: Of coating namely, one coat of Zinc
: Chromate Red oxide primer, one under
: Coating and two finishing coats.
: The system built in the above manner
: Will have an excellent durability.

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE**

KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330

Email : info@kiranpaints.com

Website : www.kiranpaints.com